

BRASS NON-RETURN AND FOOT VALVES

Spring loaded poppet type

APPLICATION

For water and clear liquids
General, Agriculture, Water distribution, Pumping

DESIGN FEATURES

- Brass casing, nitrile seal, (Viton seal for 2503, 2504)
Noryl closing system
- Screw on S/Steel strainer converts NRV to a foot valve
- Max working pressure PN10 (145 psi)
- Working temperature NRV 95°C, 190 60°C
- Exact head loss and individual technical data sheets available on request
- Can be installed at any angle
- Low water hammer generating characteristics

TECHNICAL DATA (NON-RETURN VALVE)

Part No	Type	Size
2505	NRV	20MM BSPf
2506	NRV	25MM BSPf
2507	NRV	32MM BSPf
2508	NRV	40MM BSPf
2509	NRV	50MM BSPf

TECHNICAL DATA (Strainer to make up Foot Valve)

Part No	Type	Size
5363P	101	20MM BSP
5364P	101	25MM BSP
5365	101	32MM BSP
5366	101	40MM BSP
5367	101	50MM BSP
Classic 190 foot valve complete (strainer)		
3925	190	50mm BSP

NON-RETURN VALVE (NRV)



TYPE 101 STRAINER



TYPE 190 FOOT VALVE

