



UNISAN + (UNISAN COMMERCIAL)

Fully automatic waste water pump

APPLICATION

Unisan is suitable for pumping waste water from dish-washing and washing machines (domestic and commercial), air conditioning units and from rooms which are below the sewer level, or conditions where small dimensioned discharge pipes are required.

DESIGN FEATURES

- Completely self contained
- Quiet, powerful and fully automatic
- Dry mounted motor and pump
- Easily installed and serviced
- Designed and built in New Zealand for New Zealand conditions
- 2 year warranty
- High head and flow
- Can be remotely installed
- Gas and water tight collection tank
- Multiple choice of waste inlet positions
- Can pump to a 16m head with a High Head Impeller (**optional**)
- Cold water injection for high temperature applications (**optional**)
- Audible alarm featuring phase interruption switching off auto discharging machines (**optional**)
- Solenoid valve to isolate water supply to plumbing fixtures draining to the pump (**optional**)
- Carbon filter for internal venting (**Check with your local Authority for compliance**) (**optional**)



TECHNICAL DATA

Motor Power (kW)	0.6	Total Tank Volume	25 litres
Temp Continuous / Max	60 / 95°C	Delivery connection	25mm male
Voltage 50Hz (V)	230 - 240	Delivery Pipe	25mm or 32mm PVC
Cable (m)	3.0	32mm swing check	Supplied
Nominal Current (A)	3	32mm Isolating valve	Supplied
Weight (kg)	12	Overall dimensions	485(L) x 280(W) x 400(H)

Pump Performance

