

SUBMERSIBLE WATER PUMP AquaDrain 32-750

High head, submersible clear water pump



APPLICATION

Suitable for pumping clear water, treated filtered effluent only
 NOT SUITABLE for sewage & waste water with solids

DESIGN FEATURES

- Unique **Reversed Impeller** design, ensuring **Mechanical Seal** is never subjected to high pressure from pump
- High shut off head of 33 metres
- Double mechanical seal in oil bath, operating at static head pressure only ensures reliable trouble free operation
- Unique cable sealing protects from water entering motor
- Heavy duty upper and lower ball bearings ensure smooth operation and supports axial load / thrust
- Built-in float switch for automatic liquid level operation

TECHNICAL DATA

Part Number	AD32-750	Weight (kg)	17
Motor (kW / HP)	0.75 / 1.0	Outlet (mm)	25 BSP
Power (Volts / phase)	230 - 240 / 1	Full Load Current (A)	5.24 amps
Pump Dimensions (mm)	360(H) x 250(W)	Min Sump Dimension	700x700x700mm

NOTE: Do not operate AD32-750 pump below 12m head as it may cause cavitations, vibrations etc... which may damage the pump. Such damage is not covered under warranty. For duty conditions under 12m head you may use W-400 submersible pump.

Pump Performance

