

HOT PUMP (SAN25/60) (HP / HP25)

For domestic hot water (supplied with unions 20mm / 25mm)

INSTALLATION & OPERATING CONDITIONS

Pump must be used only in clean water service without any solids, grit, or dirt. Pump to be installed such that the shaft is in a horizontal position. Pump must be installed in a weatherproof location with proper ventilation and easy access.

NB: Refer Wallace Pumps for detailed installation / operating instructions



SPECIFICATIONS

- Motor protection IP44 (must be installed in weatherproof location)
- Maximum temperature for **open systems** (65°C)
- Minimum static head must be 2.5m or more for temperatures up to 80°C, 5.0m or more for temperatures up to 95°C and 18.0m or more for temperatures up to 110°C

TECHNICAL DATA

Item No.	HP 20mm/HP25 25mm	Power P1 (W)	40w/67w/90w speed 1/2/3
Inlet (mm)	20 (25mm Optional)	Power Supply	1Ph / 230v / 50Hz
Outlet (mm)	20 (25mm Optional)	Full Load Amps	0.17/0.29/0.39 speeds 1/2/3
Casing Length	130mm W/O Unions	Max Work Press	10 bar
Casing Material	Bronze	Weight (Kg)	2.5 (Approx)
Speeds	Three	Dimensions	130mm x 130mm x 130mm

Flow Performances

