

SHOWERMMASTER BOOSTER PUMP

For domestic hot water pressure due to low pressure cylinder
For domestic cold water pressure due to header tank supply
(Supplied with Unions)



INSTALLATION & OPERATING CONDITIONS

Pump must be used only in clean water service without any solids, grit, or dirt. Pump to be installed such that the shaft is in a horizontal position. Pump must be installed in a weatherproof location with proper ventilation and easy access.

NB: Refer Wallace Pumps for detailed installation / operating instructions

SPECIFICATIONS

- In-line bronze body pump.
- Easy to install in new or existing pipelines.
- Supplied with unions, cable and NRV
- Maximum working temperature for **open systems** (65°C) for open domestic hot water circuit & **closed heating** circuit.
- Can develop Max (S.O.H) pressure of 90kPa Approx
- Low capital / operating cost
- Maximum working pressure 6 bar, Max suction pressure 4 bar
- Motor protection IP42 (must be installed in weatherproof location)
- 2 year Warranty

TECHNICAL DATA

Pump Model	SM15-9AB	Motor Size (P1/P2)	120W / 40W
Power Supply	1Ph / 230v	Full Load Amps	0.5
Inlet/Outlet	1/2" (15mm)	Max Working Press	6 bar
Weight (Kg)	3 (Approx)	Dimensions (mm)	160 x 125 x 105 (Approx)

Flow Performances



